

Toolrunner Ltd.

SPECIALIST ENGINEER SUPPLIES & MACHINE TOOL MAINTENANCE

Unit 59 Howemoss Avenue
Kirkhill Industrial Estate, Dyce
Aberdeen AB21 0GP
Tel : 01224 773000
Fax : 01224 723666

E Mail : sales@toolrunner.co.uk

www.toolrunner.co.uk

Belt Sander Type LVT






Power	Speed	Belt	Weight
1,500 Watt	2,300 – 6,500 RPM	618mm (L) x 40mm (W)	5.0 Kgs

The powerful 1.5Kw motor is controlled by a variable full wave electronic speed controller to enable a smooth, even finish on tubes and flat surfaces.

Standard Accessories:

- 1 x Surface conditioning belt SCB 618x40 Grade Medium
- 1 x Surface conditioning belt SCB 618x40 Grade Very Fine
- 2 x Corundum belt NKY 618x40 Grade 60
- 2 x Corundum belt NKY 618x40 Grade 120

Suggested Belts, 618mm (L) x 40mm (W)		
Type	Grit Size	Pack Qty
SCB – Surface Conditioning 	Coarse (80), Medium (120), Very Fine (240),	10
NKY – Corundum 	120, 80, 60, 40	20
NZY – Zirconium 	80, 60, 40	20